



**CLASSIC  
SERIES**

# VST FIELDTRAC 270D POWER PLUS

*Farmer's All Time Favourite Performer*



**POWER PACKED  
4-CYLINDER STAGE-V ENGINE:**  
MORE POWER YET ECONOMICAL



**OIL IMMERSSED BRAKE (OIB)**  
FOR EFFECTIVE SAFE AND  
RELIABLE TECHNOLOGY



**VERSATILE 8+2 TRANSMISSION**  
CAPABLE OF HANDLING MOST  
OF THE EUROPEAN APPLICATIONS



**OPTIMALLY ERGONOMISED**  
SPACIOUS & WIDE PLATFORM  
WITH EXTRA LEG ROOM



**CONVERTIBLE SINGLE/ DOUBLE  
ACTING SPOOL VALVE**



**SMART HYDRAULICS WITH ADDC:**  
750KGS LIFTING CAPACITY FOR  
HEAVY DUTY IMPLEMENTS



[exports@vstractors.com](mailto:exports@vstractors.com)



[www.vst-international.com](http://www.vst-international.com)

# TECHNICAL SPECIFICATIONS

## ENGINE

Model	V4D1E5
Emmission Norm	Stage-V
Type	Naturally Aspirated, Water Cooled 4, Stroke Diesel Engine
No. of Cylinder	4
Engine Power (HP)	24
PTO (HP)	20
Rated RPM	2700
Bore & Stroke (mm)	73 X 78
Displacement (cc)	1306
Air Cleaner	Dry Type- Dual Filter
Fuel Tank Capacity (ltrs)	18

## TRANSMISSION

Clutch	Dry Single
Gear Box Type	Sliding Mesh
Nos. of Gears	8F+2R
Gear Lever Position	Side Shift
Speed Range- km/hr	Forward: 1.77 - 21.62 Reverse: 1.58 - 5.75
Differential Lock (rear)	Standard
Brake Type	Oil Immersed Brake
Drive Type	4WD
PTO (rpm)	540 & 1000

## ELECTRICALS

Battery	12 V, 72AH, (700 CCA)
Starting system	Starter Motor 12 V , 2 KW
Alternator	12V, 35 AMP

## HYDRAULIC SYSTEM

Control Type	ADDC
Pump Capacity (LPM)	12.9
Maximum Lift Capacity (Kgs)	750
3- Point Hitch	Category-I N
Steering System	Hydraulic Assisted Power Steering
Rear Spool Valve	2 Valves with Quick Coupling

## OTHER FEATURES & DIMENSIONS

Overall Dimensions (LxBxH) with TPL	2910 x 970 x 1185
Ground Clearance (mm)	230
Turning Radius (m)	2.3
Weight (kgs)	970±50
Wheel Base (mm)	1422
Wheel Track (mm)	Front: 890 / 785 Rear: 865 / 740
Front Weight/ Ballast (kgs)	60 ( standard Fitment)
Rear Wheel Ballast (kgs)	60 ( Optional)
Tire Options ( Front & Rear Size)	Agriculture: ( 6 x12 , 8.3 x 20) Turf: (23 x 8.5, 33 X 15.5) Industrial: (23 x 8.5-12, 33 X 15.5 - 16.5)
Driver's Seat	Adjustable, European Design Seat
Operating Environment	minus 10 to plus 45 Deg C
Mobile Charging Point	Yes
Silencer ( Horizontal Position)	Yes
Battery Cut-off Switch	Yes
ROPS	Yes
Drawbar	Yes ( optional)
Hitch Assembly	Yes
Hood Lock with special key	Yes

Manufactured by:



Regd. Office.

PLOT NO- 1, DYAVASANDRA INDL. LAYOUT, WHITEFIELD ROAD,  
MAHADEVAPURA POST, BENGALURU-560048, KARNATAKA, INDIA.  
CIN- L34101KA1967PLC001706

Authorised distributors

