













COMPATIBLE ATTACHMENTS



Ridger (Furrower)



Plough



Auger (Digger)





Cultivator



Fertilizer Cum Seed Drill





Axial Flow Thresher



Bullock Type Inter Cultivator



Generator



and many more...

TECHNICAL SPECIFICATIONS

PRODUCT DETAILS	Category	Power Tiller
	Model	VST SHAKTI 130 DI
	Туре	General Purpose, Walk Behind Type
ENGINE	Туре	Four Stroke, Single Cylinder, Horizontal, Over Head Valve, Compression Ignition, Diesel Engine
	Bore × Stroke, mm	95 × 95
	Displacement, cc	673.4
	Max. Power, HP @ RPM	13 @ 2400
	Starting System	Hand Cranking (Manual)
TRANSMISSION	Transmission Drive	Gear Drive
	Туре	Combination Of Constant & Sliding Mesh
	Clutch	Dry, Multi Friction Plate
	No. of Speeds	08 (06- Forward & 02- Reverse)
	Transmission Oil Capacity, Ltr	6.0 (SAE 90)
	Brake System	Hand Operated Internal Expanding Metallic Shoe Type
	Wheels Type & Nos.	Pneumatic, Traction & 2 Nos.
	Wheels Size	6.00 - 12, 4 PR
ROTARY	No. of Tynes	18
	Rotary Speed	2
	Avg. Width of Cut, mm	600 (max.)
	Avg. Depth of Cut, mm	150 (max.)
PRODUCT OVERALL	Overall Dimension (L × W × H), mm	2370 × 880 × 1260
	Gross Weight (with rotary), Kg	430

APPLICATIONS:

Dry Land & Wet Land Operation, Inter-cultivation, Earthing-up, Land Preparation etc.

SUITABLE FOR:

Vegetable Crops, Horticulture Crops, Plantation Crops & Sugarcane





Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com, CIN: L34101KA1967PLC001706. www.vst-international.com

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.



