













SPECIAL FEATURES



Cylindrical Muffler



State Of The Art Led Head Lamps



Comfortable Seat (optional)



TECHNICAL SPECIFICATIONS

PRODUCT DETAILS	Category	Power Tiller
	Model	VST SHAKTI 135 DI ULTRA
	Туре	General Purpose, Walk Behind Type
ENGINE	Туре	Four Stroke, Single Cylinder, Horizontal, Over Head Valve, Compression Ignition, Diesel Engine
	Bore × Stroke, mm	95 × 95
	Displacement, cc	673.4
	Max. Power, HP @ RPM	13.5 @ 2400
	Starting System	Hand Cranking (Manual)
TRANSMISSION	Transmission Drive	Gear Drive
	Туре	Combination Of Constant & Sliding Mesh
	Clutch	Dry, Multi Friction Plate
	No. of Speeds	08 (06- Forward & 02- Reverse)
	Transmission Oil Capacity, Ltr	6.0 (SAE 90)
	Brake System	Hand Operated Internal Expanding Metallic Shoe Type
	Wheels Type & Nos.	Pneumatic, Traction & 2 Nos.
	Wheels Size	6.00 - 12, 4 PR
ROTARY	No. of Tynes	18
	Rotary Speed	2
	Avg. Width of Cut, mm	600 (max.)
	Avg. Depth of Cut, mm	150 (max.)
PRODUCT OVERALL	Overall Dimension (L × W × H), mm	2350 × 887 × 1340
	Gross Weight (with rotary), Kg	435

COMPATIBLE ATTACHMENTS





Sprayer

Water Pump







Generator

Reaper







Multi Crop Planter

Cage Wheel K Type





Bullock Type Inter Cultivator

Leveler



and many

Turmeric Digger

APPLICATIONS: Dry Land & Wet Land Operation, Inter-cultivation, Earthing-up, Land Preparation etc.

SUITABLE FOR: Vegetable Crops, Horticulture Crops & Plantation Crops



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com, CIN: L34101KA1967PLC001706. www.vst-international.com

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.