





Developed Heavy Duty & Robust Transmission





Aerodynamic Design & Ergonomic Seat







SPECIAL FEATURES

Hour Meter



State Of The Art Led Head Lamps



Wider Rotary



TECHNICAL SPECIFICATIONS

	Category	Power Tiller
PRODUCT DETAILS	Model	VST SHAKTI 165 DI ES POWER PLUS +
		General Purpose, Riding Type
	Туре	1 . 0 11
ENGINE	Туре	Four Stroke, Single Cylinder, Horizontal, Over Head Valve, Compression Ignition, Diesel Engine
	Bore × Stroke, mm	102 × 105
	Displacement, cc	857
	Max. Power, HP @ RPM	16.5 @ 2400
	Starting System	Hand Cranking (Manual) & Self-Start (Electric)
TRANSMISSION	Transmission Drive	Gear Drive
	Туре	Combination Of Constant & Sliding Mesh
	Clutch	Dry, Multi Friction Plate
	No. of Speeds	08 (06- Forward & 02- Reverse)
	Transmission Oil Capacity, Ltr	6.0 (SAE 90)
	Brake System	Hand Operated Internal Expanding Metallic Shoe Type
	Wheels Type & Nos.	Pneumatic, Traction & 2 Nos.
	Wheels Size	6.00 - 12, 4 PR
ROTARY	No. of Tynes	26
	Rotary Speed	2
	Avg. Width of Cut, mm	750 (max.)
	Avg. Depth of Cut, mm	150 (max.)
PRODUCT OVERALL	Overall Dimension (L × W × H), mm	2870 × 1000 × 1540
	Gross Weight (with rotary), Kg	510

APPLICATIONS: Dry Land & Wet Land Operation, Inter-cultivation, Earthing-up, Land Preparation etc.

SUITABLE FOR: Vegetable Crops, Horticulture Crops & Plantation Crops

Water Pump Sprayer



COMPATIBLE ATTACHMENTS



Generator





Multi Crop Cage Wheel K Type Planter





Bullock Type Inter Cultivator

Leveler



and many

Turmeric Digger

Authorised Dealer



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com, CIN: L34101KA1967PLC001706. www.vst-international.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

