

# **BEYOND LIMITS POWER PACKED PERFORMANCE!**



**49.5 HP**

- ◆ **POWER**
- ◆ **SAVING**
- ◆ **COMFORT**



ROBUST  
3-CYLINDER  
ENGINE



OIL  
IMMERSED  
BRAKES



POWER STEERING  
EASE FOR  
TURNING



SMART HYDRAULIC  
SYSTEM WITH  
ADDC



HEAVY DUTY  
REAR AXLE



COMFORTABLE &  
ADJUSTABLE SEAT





# VIRAAJ 9054DI

## SPECIFICATIONS

### ENGINE

Power, HP	:	<b>49.5</b>
No. of Cylinders	:	<b>3</b>
Cubic Capacity, cc	:	<b>3120</b>
Engine RPM	:	<b>2200</b>
Air cleaner	:	<b>Dry Type</b>

### POWER TAKE OFF

Power, HP	:	<b>45</b>
PTO Std.	:	<b>540</b>

### TRANSMISSION

Type	:	<b>Sliding Mesh</b>
No. of Speeds	:	<b>8F + 2R</b>
Rear Axle Reduction Type	:	<b>Bull gear</b>

### SPEED & CLUTCH

Forward Speed, kmph	:	<b>2.4 - 34</b>
Reverse Speed, kmph	:	<b>3.0 - 11.9</b>
Clutch Type	:	<b>Dual Clutch</b>

### BRAKES

Brake Type	:	<b>OIB</b>
------------	---	------------

### STEERING TYPE

Type	:	<b>Power Steering</b>
------	---	-----------------------

### HYDRAULICS

Type	:	<b>ADDC</b>
Lift Capacity	:	<b>1800</b>
3 Point Linkage	:	<b>CAT-II</b>

### TYRE

Front	:	<b>6.5x16/7.5x16*</b>
Rear	:	<b>14.9x28/16.9x28*</b>

### WEIGHTS & DIMENSIONS

Length, mm	:	<b>3875</b>
Width, mm	:	<b>1890</b>
Height, mm	:	<b>2250</b>
Wheelbase, mm	:	<b>2200</b>
Ground Clearance, mm	:	<b>440</b>
Weight, Kg	:	<b>2345</b>



Trust of >5 Lakh Farmers,  
Legacy of >50 Years



Widest Product Range  
(2 HP to 50 HP)



No.1 Power Tiller Brand  
for Last 50 Years



Pioneer in 4WD  
Compact Tractors



Global Footprints  
in > 40 Countries



Year on Year Growth  
Rate > 20%



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,  
Mahadevapura Post, Bengaluru-560048, Karnataka, INDIA  
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com,  
CIN: L34101KA1967PLC001706. [www.vsttractors.com](http://www.vsttractors.com)

[f /vsttillers](https://www.facebook.com/vsttillers) [in /company/vst-tillers](https://www.linkedin.com/company/vst-tillers)

<http://bit.ly/VSTVideos>

**Disclaimer :** Pictures used here are for illustration purpose only. Product specification are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

