

NEW AND STYLISH



4WD **18 HP**



SHORTER TURNING RADIUS



SMART HYDRAULICS WITH ADDC



DIRECT CONTROL VALVE



SIDE SHIFT



DUAL PROJECTOR HEADLAMPS



COMFORTABLE & ADJUSTABLE SEAT



BONNET WITH LOCK



MOBILE CHARGING POINT



TURF, INDUSTRIAL & AGRICULTURE TYRE OPTIONS



SPECIFICATIONS

ENGINE

Power, HP : 18
 No. of Cylinders : 3
 Cubic Capacity, cc : 900
 Max. Torque : 48.3
 Engine RPM : 2700
 Air cleaner : Dry Type

POWER TAKE OFF

Power, HP : 11.1
 Pto Std. : 540

TRANSMISSION

Type : Sliding Mesh
 No. of Speeds : 6F + 2R
 Rear Axle Reduction Type : Bull Gear
 Differential Lock : Yes

SPEED & CLUTCH

Forward Speed, kmph : 1.53 - 17.3
 Reverse Speed, kmph : 1.95 - 8.53
 Clutch Type : Single

BRAKES

Brake Type : Dry Drum type

STEERING TYPE

Type : Power Steering

SEAT

Type : Adjustable driver seat

HYDRAULICS

Type : ADDC
 Lift Capacity : 500 Kg
 3 Point Linkage : CAT-I
 Hydraulic Valve Type : 1SA/1DA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm : 2945
 Width, mm : 1097
 Height, mm : 2120
 Wheelbase, mm : 1420
 Ground Clearance, mm : 255
 Weight, Kg : 880
 Turning Radius, m : 2.3

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Engine Shut-off with Key
- Double acting rear hydraulic remote (DCV)
- Bonnet with Lock
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	5 x 12	8 x 18
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%

