

**COMPACT.
POWERFUL.
UNSTOPPABLE!**



4WD 22 HP



SIDE SHIFT



SHORTEST TURNING RADIUS IN ITS CATEGORY



SMART HYDRAULICS WITH ADDC



DUAL PROJECTOR HEADLAMPS



HEAVY DUTY FRONT AXLE



DIRECT CONTROL VALVE



COMFORTABLE & ADJUSTABLE SEAT



MOBILE CHARGING POINT



BONNET WITH LOCK



TURF, INDUSTRIAL & AGRICULTURE TYRE OPTIONS



SPECIFICATIONS

ENGINE

Power, HP	:	22
No. of Cylinders	:	3
Cubic Capacity, cc	:	980
Max. Torque	:	54
Engine RPM	:	3000
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	12.2
Pto Std.	:	540

TRANSMISSION

Type	:	Sliding Mesh
No. of Speeds	:	6F + 2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.7-19.2
Reverse Speed, kmph	:	2.2-9.5
Clutch Type	:	Single

BRAKES

Brake Type	:	Dry Drum type
------------	---	---------------

STEERING TYPE

Type	:	Power Steering
------	---	----------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	500
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	ISA/IDA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2945
Width, mm	:	1130
Height, mm	:	2330
Wheelbase, mm	:	1420
Ground Clearance, mm	:	267
Weight, Kg	:	880
Turning Radius, m	:	2.3

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Engine Shut-off with Key
- Rear View Mirror
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	6 x 12	8.3 x 20
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%

